

BODY BIKE SMART

Max user hight 220 cm / 7.2 ft Max user weight 150 kg / 331 lbs Q-factor 168 mm / 6.6 in



Containin recycled ABS

KEY SPECIFICS

| | | | | | |
|---------------|--------|---------------------|---------------------------|----------------------|----------------------|
| Hight | 99 cm | Drive train | Kevlar Poly V-belt | Data transfer | - |
| Lenght | 106 cm | Brake system | Kevlar break pad | Data display | LCD Console optional |
| Width | 56 cm | Crank hub | Recycled cast iron | Power | If sensor: Batteries |
| Weight | 64 kg | Bearings | High quality SKF bearings | Charge | No |

DIMENSIONS

| | |
|------------------|--------------------|
| Hight | 99 cm / 39 in |
| Lenght | 106 cm / 41 in |
| Width | 56 cm / 23 in |
| Weight | 64 kg / 141 lbs |
| Q-factor | 168 mm / 6.6 in |
| Footprint | 0.63 m2 / 6.79 ft2 |

FRAME

| | |
|--------------------------|---|
| Side covers | Containing recycled ABS |
| Frame | Robot welded |
| Front tube | Stainless steel |
| Sadel tube | Steel |
| Other frame tubes | Steel |
| Frame coating | Black powder coated fully protected by side covers |
| Posts | Anodized aluminium |
| Stabilisers | Shot-blasted, primed and powder coated |
| Frame mounting | Stainless steel |

TOUCH POINTS

| | |
|---------------------------|---|
| Handelbar | Powder coated stainless steel rubber-coated |
| Aerobars | Black aluminium, extended version |
| Levelling feet | Adjustable rubber feet stainless steel fitting |
| Transport wheels | With heavy duty bearings D:75 mm |
| Adjustments | Vertical & horizontal |
| Bike fit | Power position |
| Saddle | Double density, shock absorbing, unisex |
| Thumb screw | No |
| Bottle holder | Smart Dock phone & tablet holder |
| Adjustment handles | Smart release |
| Service hatch | 4-point magnetic |
| Stretch area | Reinforced stretch area at the rear end of bike |
| Pedals | SPD, SPD/Look, Standard |

BIKE TECHNOLOGY

| | |
|----------------------|----------------------|
| Data display | LCD Console optional |
| Sensors | - |
| Power supply | If sensor: Batteries |
| Charge option | No |
| Data transfer | If sensor: ANT+ |

INTERIOR

| | |
|------------------------|--------------------------------|
| Drive train | Poly V-belt with Kevlar |
| Brake system | Friction with kevlar break pad |
| Crank hub | Processed cast iron, patented |
| Bearings | High quality SKF bearings |
| Crank/Pedalarm | Cast iron 170 mm / 6,6 inch |
| Flywheel | 16 kg / 35 lbs cast iron |
| Emergency brake | Push |

COLOR & STYLING

Signature styling option

Simple logo / full hatch

Full colour



Top colour

